

Docket No. AUS920010976US1

**METHOD, APPARATUS, AND PROGRAM FOR QUICK SAVE TO REMOTE  
STORAGE**

**BACKGROUND OF THE INVENTION**

**1. Technical Field:**

5       The present invention relates to data processing and, in particular, to managing files in a data processing system. Still more particularly, the present invention provides a method, apparatus, and program for allowing quick saving of files to remote storage.

10   **2. Description of Related Art:**

          In the course of using a client device, the user may encounter several documents or files that will be required at another location. Typically, the user would need to transfer those files to a removable storage  
15   device or mobile device. However, the files may be scattered across several directories, folders, drives, or even servers. Thus, to collect the files onto a removable storage device or mobile device requires using an interface for copying the files from its location to  
20   the appropriate destination. Even simply the documents or files while they are open in an application requires navigating a save dialog to locate the destination device.

          Furthermore, if only a portion of a document or file  
25   is desired, the user must either save the entire file or create another version of the document or file containing only the desired portion. Creating this second file or document may require several tedious steps, such as creating a new document, copying a selected portion,

Docket No. AUS920010976US1

pasting the copied portion, etc. Then, the user must navigate the save dialog to locate the destination device, as stated above.

Still further, to have a portable copy of needed  
5 files, the user must physically carry the removable  
storage device or mobile device. When the user then  
wishes to access those files at another client device,  
the client device must be able to read the removable  
storage device or must be configured with an interface  
10 for the mobile device. The user also risks losing the  
removable storage device or mobile device. For these  
reasons, creating a portable copy of needed files is  
inconvenient and unreliable.

Therefore, it would be advantageous to provide an  
15 improved mechanism for creating a portable copy of files.

10045897 10045897

Docket No. AUS920010976US1

### SUMMARY OF THE INVENTION

The present invention provides a remote save mechanism that allows a user to transfer a document or file or a portion thereof to a predetermined directory or folder from the interface of an application. The contents of the document or file may be stored in a file format that is consistent with the application or with the original file. If a portion is selected for transfer to the predetermined directory or folder, the portion may be stored in a file format that is consistent with the selected portion.

The remote save mechanism may be configured to synchronize the contents of the predetermined directory or folder with a remotely located copy either periodically or in response to a request from the user. The remotely located copy may be managed by a server. The remote server may require authentication for the user to access the remotely located copy of files. The user may then access the files from any location without the need for removable media or mobile devices.

**BRIEF DESCRIPTION OF THE DRAWINGS**

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

**Figure 1** depicts a pictorial representation of a network of data processing systems in which the present invention may be implemented;

**Figure 2** is a block diagram of a data processing system that may be implemented as a server in accordance with a preferred embodiment of the present invention;

**Figure 3** is a block diagram illustrating a data processing system in which the present invention may be implemented;

**Figures 4A and 4B** depict example screens of display of an application window in accordance with a preferred embodiment of the present invention;

**Figure 5** is an example screen of display of a remote access window in accordance with a preferred embodiment of the present invention;

**Figure 6** is an exemplary block diagram of a data processing system with quick remote save in accordance with a preferred embodiment of the present invention;

**Figures 7A and 7B** are flowcharts illustrating the operation of a remote save mechanism in accordance with a preferred embodiment of the present invention; and

Docket No. AUS920010976US1

**Figure 8** is a flowchart illustrating the operation of a remote server in accordance with a preferred embodiment of the present invention.

1004 1003 1002 1001 1000 999 998 997 996 995 994 993 992 991 990 989 988 987 986 985 984 983 982 981 980 979 978 977 976 975 974 973 972 971 970 969 968 967 966 965 964 963 962 961 960 959 958 957 956 955 954 953 952 951 950 949 948 947 946 945 944 943 942 941 940 939 938 937 936 935 934 933 932 931 930 929 928 927 926 925 924 923 922 921 920 919 918 917 916 915 914 913 912 911 910 909 908 907 906 905 904 903 902 901 900 899 898 897 896 895 894 893 892 891 890 889 888 887 886 885 884 883 882 881 880 879 878 877 876 875 874 873 872 871 870 869 868 867 866 865 864 863 862 861 860 859 858 857 856 855 854 853 852 851 850 849 848 847 846 845 844 843 842 841 840 839 838 837 836 835 834 833 832 831 830 829 828 827 826 825 824 823 822 821 820 819 818 817 816 815 814 813 812 811 810 809 808 807 806 805 804 803 802 801 800 799 798 797 796 795 794 793 792 791 790 789 788 787 786 785 784 783 782 781 780 779 778 777 776 775 774 773 772 771 770 769 768 767 766 765 764 763 762 761 760 759 758 757 756 755 754 753 752 751 750 749 748 747 746 745 744 743 742 741 740 739 738 737 736 735 734 733 732 731 730 729 728 727 726 725 724 723 722 721 720 719 718 717 716 715 714 713 712 711 710 709 708 707 706 705 704 703 702 701 700 699 698 697 696 695 694 693 692 691 690 689 688 687 686 685 684 683 682 681 680 679 678 677 676 675 674 673 672 671 670 669 668 667 666 665 664 663 662 661 660 659 658 657 656 655 654 653 652 651 650 649 648 647 646 645 644 643 642 641 640 639 638 637 636 635 634 633 632 631 630 629 628 627 626 625 624 623 622 621 620 619 618 617 616 615 614 613 612 611 610 609 608 607 606 605 604 603 602 601 600 599 598 597 596 595 594 593 592 591 590 589 588 587 586 585 584 583 582 581 580 579 578 577 576 575 574 573 572 571 570 569 568 567 566 565 564 563 562 561 560 559 558 557 556 555 554 553 552 551 550 549 548 547 546 545 544 543 542 541 540 539 538 537 536 535 534 533 532 531 530 529 528 527 526 525 524 523 522 521 520 519 518 517 516 515 514 513 512 511 510 509 508 507 506 505 504 503 502 501 500 499 498 497 496 495 494 493 492 491 490 489 488 487 486 485 484 483 482 481 480 479 478 477 476 475 474 473 472 471 470 469 468 467 466 465 464 463 462 461 460 459 458 457 456 455 454 453 452 451 450 449 448 447 446 445 444 443 442 441 440 439 438 437 436 435 434 433 432 431 430 429 428 427 426 425 424 423 422 421 420 419 418 417 416 415 414 413 412 411 410 409 408 407 406 405 404 403 402 401 400 399 398 397 396 395 394 393 392 391 390 389 388 387 386 385 384 383 382 381 380 379 378 377 376 375 374 373 372 371 370 369 368 367 366 365 364 363 362 361 360 359 358 357 356 355 354 353 352 351 350 349 348 347 346 345 344 343 342 341 340 339 338 337 336 335 334 333 332 331 330 329 328 327 326 325 324 323 322 321 320 319 318 317 316 315 314 313 312 311 310 309 308 307 306 305 304 303 302 301 300 299 298 297 296 295 294 293 292 291 290 289 288 287 286 285 284 283 282 281 280 279 278 277 276 275 274 273 272 271 270 269 268 267 266 265 264 263 262 261 260 259 258 257 256 255 254 253 252 251 250 249 248 247 246 245 244 243 242 241 240 239 238 237 236 235 234 233 232 231 230 229 228 227 226 225 224 223 222 221 220 219 218 217 216 215 214 213 212 211 210 209 208 207 206 205 204 203 202 201 200 199 198 197 196 195 194 193 192 191 190 189 188 187 186 185 184 183 182 181 180 179 178 177 176 175 174 173 172 171 170 169 168 167 166 165 164 163 162 161 160 159 158 157 156 155 154 153 152 151 150 149 148 147 146 145 144 143 142 141 140 139 138 137 136 135 134 133 132 131 130 129 128 127 126 125 124 123 122 121 120 119 118 117 116 115 114 113 112 111 110 109 108 107 106 105 104 103 102 101 100 99 98 97 96 95 94 93 92 91 90 89 88 87 86 85 84 83 82 81 80 79 78 77 76 75 74 73 72 71 70 69 68 67 66 65 64 63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

With reference now to the figures, **Figure 1** depicts a pictorial representation of a network of data processing systems in which the present invention may be implemented.

5 Network data processing system **100** is a network of computers in which the present invention may be implemented. Network data processing system **100** contains a network **102**, which is the medium used to provide communications links between various devices and computers  
10 connected together within network data processing system **100**. Network **102** may include connections, such as wire, wireless communication links, or fiber optic cables.

In the depicted example, server **104** is connected to network **102** along with storage unit **106**. In addition,  
15 clients **108**, **110**, and **112** are connected to network **102**. These clients **108**, **110**, and **112** may be, for example, personal computers or network computers. In the depicted example, server **104** provides data, such as boot files, operating system images, and applications to clients  
20 **108-112**. Clients **108**, **110**, and **112** are clients to server **104**. Network data processing system **100** may include additional servers, clients, and other devices not shown. In the depicted example, network data processing system **100** is the Internet with network **102** representing a  
25 worldwide collection of networks and gateways that use the TCP/IP suite of protocols to communicate with one another. At the heart of the Internet is a backbone of high-speed data communication lines between major nodes or host computers, consisting of thousands of commercial,  
30 government, educational and other computer systems that

Docket No. AUS920010976US1

route data and messages. Of course, network data processing system 100 also may be implemented as a number of different types of networks, such as for example, an intranet, a local area network (LAN), or a wide area network (WAN). **Figure 1** is intended as an example, and not as an architectural limitation for the present invention.

Referring to **Figure 2**, a block diagram of a data processing system that may be implemented as a server, such as server 104 in **Figure 1**, is depicted in accordance with a preferred embodiment of the present invention. Data processing system 200 may be a symmetric multiprocessor (SMP) system including a plurality of processors 202 and 204 connected to system bus 206. Alternatively, a single processor system may be employed. Also connected to system bus 206 is memory controller/cache 208, which provides an interface to local memory 209. I/O bus bridge 210 is connected to system bus 206 and provides an interface to I/O bus 212. Memory controller/cache 208 and I/O bus bridge 210 may be integrated as depicted.

Peripheral component interconnect (PCI) bus bridge 214 connected to I/O bus 212 provides an interface to PCI local bus 216. A number of modems may be connected to PCI local bus 216. Typical PCI bus implementations will support four PCI expansion slots or add-in connectors. Communications links to clients 108-112 in **Figure 1** may be provided through modem 218 and network adapter 220 connected to PCI local bus 216 through add-in boards.

Additional PCI bus bridges 222 and 224 provide interfaces for additional PCI local buses 226 and 228, from which additional modems or network adapters may be

Docket No. AUS920010976US1

supported. In this manner, data processing system 200 allows connections to multiple network computers. A memory-mapped graphics adapter 230 and hard disk 232 may also be connected to I/O bus 212 as depicted, either  
5 directly or indirectly.

Those of ordinary skill in the art will appreciate that the hardware depicted in **Figure 2** may vary. For example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or in  
10 place of the hardware depicted. The depicted example is not meant to imply architectural limitations with respect to the present invention.

The data processing system depicted in **Figure 2** may be, for example, an IBM e-Server pSeries system, a  
15 product of International Business Machines Corporation in Armonk, New York, running the Advanced Interactive Executive (AIX) operating system or LINUX operating system.

With reference now to **Figure 3**, a block diagram  
20 illustrating a data processing system is depicted in which the present invention may be implemented. Data processing system 300 is an example of a client computer. Data processing system 300 employs a peripheral component interconnect (PCI) local bus architecture. Although the  
25 depicted example employs a PCI bus, other bus architectures such as Accelerated Graphics Port (AGP) and Industry Standard Architecture (ISA) may be used. Processor 302 and main memory 304 are connected to PCI local bus 306 through PCI bridge 308. PCI bridge 308 also  
30 may include an integrated memory controller and cache memory for processor 302. Additional connections to PCI local bus 306 may be made through direct component



Docket No. AUS920010976US1

interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter 310, SCSI host bus adapter 312, and expansion bus interface 314 are connected to PCI local bus 306 by direct component

5 connection. In contrast, audio adapter 316, graphics adapter 318, and audio/video adapter 319 are connected to PCI local bus 306 by add-in boards inserted into expansion slots. Expansion bus interface 314 provides a connection for a keyboard and mouse adapter 320, modem 322, and  
10 additional memory 324. Small computer system interface (SCSI) host bus adapter 312 provides a connection for hard disk drive 326, tape drive 328, and CD-ROM drive 330. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

15 An operating system runs on processor 302 and is used to coordinate and provide control of various components within data processing system 300 in **Figure 3**. The operating system may be a commercially available operating system, such as Windows 2000, which is available from  
20 Microsoft Corporation. An object oriented programming system such as Java may run in conjunction with the operating system and provide calls to the operating system from Java programs or applications executing on data processing system 300. "Java" is a trademark of Sun  
25 Microsystems, Inc. Instructions for the operating system, the object-oriented operating system, and applications or programs are located on storage devices, such as hard disk drive 326, and may be loaded into main memory 304 for execution by processor 302.

30 Those of ordinary skill in the art will appreciate that the hardware in **Figure 3** may vary depending on the

Docket No. AUS920010976US1

implementation. Other internal hardware or peripheral devices, such as flash ROM (or equivalent nonvolatile memory) or optical disk drives and the like, may be used in addition to or in place of the hardware depicted in

- 5 **Figure 3.** Also, the processes of the present invention may be applied to a multiprocessor data processing system.

As another example, data processing system 300 may be a stand-alone system configured to be bootable without  
10 relying on some type of network communication interface, whether or not data processing system 300 comprises some type of network communication interface. As a further example, data processing system 300 may be a personal digital assistant (PDA) device, which is configured with  
15 ROM and/or flash ROM in order to provide non-volatile memory for storing operating system files and/or user-generated data.

The depicted example in **Figure 3** and above-described examples are not meant to imply architectural  
20 limitations. For example, data processing system 300 also may be a notebook computer or hand held computer in addition to taking the form of a PDA. Data processing system 300 also may be a kiosk or a Web appliance.

In the course of using a client device, the user may  
25 encounter several data items, such as documents or files, that will be required at another location. Typically, the user would need to transfer those data items to a removable storage device or mobile device. However, the data items may be scattered across several directories,  
30 folders, drives, or even servers. Thus, to collect the data items onto a removable storage device or mobile device requires using an interface for copying the files

Docket No. AUS920010976US1

from its location to the appropriate destination. Even simply the documents or files while they are open in an application requires navigating a save dialog to locate the destination device.

5 Furthermore, if only a portion of a data item is desired, the user must either save the entire file or create another version of the data item containing only the desired portion. Creating this second file or document may require several tedious steps, such as  
10 creating a new document, copying a selected portion, pasting the copied portion, etc. Then, the user must navigate the save dialog to locate the destination device, as stated above.

Still further, to have a portable copy of needed  
15 files, the user must physically carry the removable storage device or mobile device. When the user then wishes to access those files at another client device, the client device must be able to read the removable storage device or must be configured with an interface  
20 for the mobile device. The user also risks losing the removable storage device or mobile device. For these reasons, creating a portable copy of needed files is inconvenient and unreliable.

Example screens of display of an application window  
25 are shown in **Figures 4A** and **4B** in accordance with a preferred embodiment of the present invention. Particularly, with reference to **Figure 4A**, the screen comprises window **400**, including a title bar **402**, which may display the name of the application program. Title  
30 bar **402** also includes a control box **404**, which produces a drop-down menu (not shown) when selected with the mouse, and "minimize" **406**, "maximize" or "restore" **408**, and

Docket No. AUS920010976US1

"close" 410 buttons. The "minimize" and "maximize" or "restore" buttons 406 and 408 determine the manner in which the program window is displayed. In this example, the "close" button 410 produces an "exit" command when  
5 selected. The drop-down menu produced by selecting control box 404 includes commands corresponding to "minimize," "maximize" or "restore," and "close" buttons, as well as "move" and "resize" commands.

Application window 400 also includes a menu bar 412.  
10 Menus to be selected from menu bar 412 may include "File," "Edit," "View," "Insert," "Format," "Tools," "Window," and "Help." However, menu bar 412 may include fewer or more menus, as understood by a person of ordinary skill in the art. The application window  
15 display area includes a display area 416 in which a document or file is displayed.

Window 400 also includes tool bar 414 for displaying buttons that may be selected to perform frequently used functions. In accordance with a preferred embodiment of  
20 the present invention, "Remote Save" button 418 is added to the tool bar by installing a plug-in for the graphical user interface of the application. The application vendor may release application program interfaces (API) to enable plug-ins. When the user selects button 418,  
25 the document or file displayed in display area 416 is saved or copied to a predetermined remote save directory or folder. The button may also be associated with a keyboard shortcut or voice command to allow the user to quickly and easily save the document or file, or portion  
30 thereof, with a single action.

Alternatively, the user may select a portion of the

Docket No. AUS920010976US1

document or file. **Figure 4B** shows an example screen of display of an application in which a portion of a displayed document is selected. Application window **450** displays a document. Portion **466** is selected by a user.

- 5 If "Remote Save" button **468** is selected while the portion is selected, the remote save mechanism may create a new version of the document containing the selected portion.

The portion may be stored in a file format that is consistent with the selected portion. For example, if a portion of text is selected, the portion may be stored as a text file or in a format that is consistent with the application or original document. If an image is selected within a document, the selected content may be stored in an image format, such as bitmap or graphics interchange format (GIF) for example.

10  
15

In the example shown in **Figure 4B**, the document is textual. The selected portion may be stored in a format that is consistent with the original document, such as rich text format (RTF). Alternatively, the portion may be stored as a text file. The manner in which portions are saved may be defined by the user.

20

The remote save mechanism may be configured to synchronize the contents of the remote save directory or folder with a remotely located copy either periodically or in response to a request from the user. The remotely located copy may be managed by a server. The remote server may require authentication for the user to access the remotely located copy of files. The user may then access the files from any location without the need for removable media or mobile devices.

25  
30

With reference to **Figure 5**, an example screen of display of a remote access window is shown in accordance

Docket No. AUS920010976US1

with a preferred embodiment of the present invention. Remote access window 500 includes display area 516 in which local and remote copies of files are stored. The remote files may be stored on a server, such as a network  
5 file server or Web server. The server may be, for example, server 104 in **Figure 1**. The server may require authentication information from the user before granting access to the remote files. Thus, the server may save account information for users. The account information  
10 may include the authentication information, such as a user name and password, and the location on the server for that user's remote files.

The local files are the files stored in the remote save directory. These files may be updated versions of  
15 files already stored remotely or may be new files to be saved on the server. The user may initiate synchronization of the files by selecting "Sync" button 518. The synchronization between remote and local copies of the files may then be performed using known transfer  
20 protocols, such as File Transfer Protocol (FTP), or a protocol specifically designed for the remote save mechanism. In an alternative embodiment of the present invention, synchronization may be performed automatically on a periodic basis or when the operating system shuts  
25 down.

The interface shown in **Figure 5** may also be used to manage the files in the remote storage. For example, the user may delete files that are no longer needed, rename files, move or copy files to other locations, etc. The  
30 user may also manage files in the remote save directory before synchronizing.

**Figure 6** is an exemplary block diagram of a data

Docket No. AUS920010976US1

processing system with quick remote save in accordance with a preferred embodiment of the present invention. Data processing system 600 includes a controller 602, a display interface 604, a user interface 606, a  
5 communications interface 608, an application 610, and a remote save tool 612. The elements 602-612 may be implemented as hardware, software, or a combination of hardware and software. In a preferred embodiment, the elements 602-612 are implemented as software instructions  
10 executed by one or more processors.

The elements 602-612 are coupled to one another via the control/data signal bus 620. Although a bus architecture is shown in **Figure 6**, the present invention is not limited to such. Rather, any architecture that  
15 facilitates the communication of control/data signals between elements 602-612 may be used without departing from the spirit and scope of the present invention. The controller 602 controls the overall operation of the document viewer and orchestrates the operation of the  
20 other elements 604-612.

With the operation of the present invention, application 610 instructs controller 602 to display a document or file via display interface 604. The user interacts with the application via user interface 606.  
25 Remote save tool 612, when enabled, allows the user to quickly save a document or file of interest, or a portion thereof, to remote save directory 616. This may be achieved by adding a button to application 610 and user interface 606. The user may then perform the save by  
30 selecting the button, thus allowing the user to save the desired content with a single click of a mouse or other

Docket No. AUS920010976US1

action.

Application 610 may retrieve documents from a remote location. For example, the document viewer may be a Web browser. Thus, data processing system 600 may receive  
5 documents to display from communications interface 608.

The remote save tool may be a plug-in for application 610. In accordance with a preferred embodiment of the present invention, remote save tool 612  
10 may also include an interface for allowing a user to synchronize contents of remote save directory 616 with a copy on a remote server through communications interface 608. The remote server may be a network file server or Web server. The server may require authentication information from the user before granting access to the  
15 remote files.

The location of the server, authentication information, and the location of the remote save directory may be stored in preferences 614. The preference may also include other information, such as  
20 whether files are to be synchronized automatically, the frequency with which files are to be synchronized, etc.

In an alternative embodiment, data processing system 600 may support a multi-user environment. In this case, preferences for multiple users may be stored in  
25 preferences 614. Thus, a first user may sign into the system, store files in a first directory, and automatically synchronize those files to a first remote server with a first username and password. A second user may sign into the system, store files in a second  
30 directory, and synchronize those files to a second remote server with a second username and password in response to an action by the second user.



Docket No. AUS920010976US1

In another embodiment, a user may wish to synchronize the remote directory to another storage device that is either located either locally or remotely. For example, a user may wish to synchronize the contents of the remote save directory with a removable storage device, such as a floppy disk, or a mobile device, such as a personal digital assistant (PDA). Thus, preferences 614 may include a profile (set of user preferences) that designates a removable storage device or mobile device as the remote storage.

With reference now to **Figures 7A** and **7B**, flowcharts illustrating the operation of a remote save mechanism are shown in accordance with a preferred embodiment of the present invention. Particularly, with respect to **Figure 7A**, the operation of a remote save plug-in for an application is shown. The process begins and starts an application (step 702). Then, the process adds a remote save button to the tool bar or button bar of the application (step 704) and loads user preferences (step 706).

Next, a determination is made as to whether the button is selected (step 708). If the button is selected, a determination is made as to whether a portion of a file or document is selected in the application (step 710). If a portion of the document or file is selected, the process creates a file for the portion (step 712), moves the file to the remote save directory or folder (step 714), and returns to step 708 to determine if the button is selected. If, however, a portion of a document or file is not selected in step 710, the process moves the file that is open in the

Docket No. AUS920010976US1

application to the remote save directory (step 714) and returns to step 708 to determine whether the button is selected.

Returning to step 708, if the button is not  
5 selected, a determination is made as to whether an exit condition exists (step 716). If an exit condition exists, the process ends. If an exit condition does not exist in step 716, the process returns to step 708 to determine whether the button is selected.

10 With reference to **Figure 7B**, a flowchart of the operation of synchronization in the remote save mechanism is shown. The process begins when a synchronization condition exists. A synchronization condition may be, for example, the selection of a synchronization button on  
15 a user interface or the expiration of a timer. For example, the remote save mechanism may be configured to synchronize the remote save directory with a copy on a remote server every ten minutes.

When a synchronization condition is received, the  
20 process establishes a connection to the server (step 722). Thereafter, the process synchronizes the files (step 724) and ends. Synchronization of the files may simply comprise moving or copying the files from the remote save directory to the remote server. However,  
25 synchronization may also consists of copying files from the server to the remote save directory on the local machine if the remote copy is more recent.

Turning to **Figure 8**, a flowchart illustrating the operation of a remote server is shown in accordance with  
30 a preferred embodiment of the present invention. The process begins when an access request is received. Then, the process authenticates a user (step 802). A

Docket No. AUS920010976US1

determination is made as to whether the user is authenticated (step 804). If the user is authenticated, the process permits access to the files on the remote server (step 806). However, if the user is not  
5 authenticated in step 804, the process denies access (step 808) and ends.

Thus, the present invention solves the disadvantages of the prior art by providing a remote save mechanism that allows a user to designate a document or file, or a  
10 portion thereof, to be saved in a remote location. If only a portion of a file is to be saved, the remote save mechanism performs the actions necessary to save only the portion. The present invention allows the user to store a file or document at a remote location with a single  
15 action, such as a single mouse click or key sequence. Furthermore, the remote copy of the files or documents may be accessed at any location. For example, if the files are stored on a Web server or FTP server, the user may then access the files from any computer with an  
20 Internet connection.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of  
25 the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the  
30 distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and

Docket No. AUS920010976US1

transmission-type media, such as digital and analog communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The  
5 computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

The description of the present invention has been presented for purposes of illustration and description,  
10 and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention,  
15 the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.